
5MP AHD HA-DVR-5108/16-L

FEATURES

- H.265+ dual-stream video compression
- Supports HDCVI/TVI/AHD/CVBS video inputs
- Long transmission distance over coax cable
- Supports 1 SATA HDD, up to 10TB



SAFETY FEATURES

- Configurable motion detection and camera tamper detection settings, including configurable event notifications, such as automatic emails (with attached video or snapshot) and automatic alerts (such as buzzers).
- Remote configuration and firmware updating through Honeywell Viewer web client and the Honeywell Config tool. Password-protected access to the camera's and DVR's video and network setup.
- Bidirectional communication for the DVR.

EASY TO USE

- The Quick wizard and plug-and-play (like traditional DVRs and analog cameras) make setup fast and easy.
- Physical installation within minutes with the help of a comprehensive and easy-to-understand quick installation guide.



DYNAMIC, ACCESSIBLE MONITORING

- Monitor from anywhere using the mobile apps for iOS and Android devices.
- The DVR support feature of smart search (search for video that was recorded because motion was detected in a selected area).

MARKET OPPORTUNITIES

- The AHD 5MP DVRs' technology makes these recorders perfect for installations where you want HD-quality video while still using your existing coax infrastructure.
- These AHD DVRs also deliver higher quality video than current 960H analog systems, but at a similar cost.

FULLY-FEATURED DVRs



High decoding capability for full HD viewing.



H.265+ video compression.



DVR supports multi format AHD/CVI/TVI/CVBS video input.



Simultaneous

HDMI/VGA video output.



5MP AHD HA-DVR-5108/16-L

TECHNICAL SPECIFICATIONS

SYSTEM		NETWORK		
			00014 D1 (5 D. (440011)	
Main Processor	Embedded Processor Embedded I INUX	Ethernet	8CH: 1 RJ-45 Port (100M) 16CH: 1 RJ-45 Port (1000M)	
Operating System	Embedded Linux	Network Function	HTTPS; TCP/IP; IPv4/IPv6; UPnP; RTSP; UDP; SMTP; NTP; DHCP; DNS; IP filter; PPPoE; DDNS; FTP; IP Search	
VIDEO AND AUDIO		Max. User Access	128 users	
Analog Camera Input	8/16 Channel, BNC	Smart Phone	iPhone, iPad, Android (phone and tablet)	
AHD Camera	5MP, 4MP, 1080P@25/30, 720P@25/30fps	Interoperability	ONVIF Conformant	
CVBS Camera	PAL/NTSC	VIDEO DETECTION AN	ND ALARM	
Audio In/Out	1/1, RCA	Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips	
Two-way Talk	Reuse audio in/out, RCA	Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss, Tampering and Diagnosis	
RECORDING		PLAYBACK AND BAC	KUP	
Video Compression	H.265+/H.265/H.264+/H.264	Playback	8CH: 1/4/9	
Resolution	5M-N, 4M-N, 1080P, 1080N, 720P, 960H, D1, CIF		16CH: 1/4/9/16	
Record Rate	Main stream:5M-N(1~10fps), 4M-N/1080P(1~15fps), 1080N/720P/960H/D1/CIF (1~25/30fps) Sub stream:	Search Mode	Time/Date; Alarm; Motion Detection; Exact Search (accurate to a second)	
Video Bit Rate	D1/CIF(1~15fps) 32Kbps~6144Kbps Per Channel	Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, Previous File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom	
Record Mode	Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop	Backup Mode	USB Device/Network	
		ELECTRICAL		
Record Interval	1 ~ 60 min (default: 60 min), Pre-record: 1 ~ 30 sec, Post-record: 10 ~ 300 sec	Power Supply	DC12V/1.5A	
Audio Compression	AAC(only for the 1st channel), G.711A, G.711U, PCM	Power Consumption (without HDD)	8CH:<10W 16CH:<15W	
Audio Sample Rate	8KHz, 16 bit Per Channel			
Audio Bit Rate	64Kbps Per Channel	Dimensions	Compact 1U, 260×236×48mm(10.2"×9.3"×1.9")	
DISPLAY		Net Weight(without HDD)	8CH:1.0kg (2.6 lb) 16CH:1.1kg(2.9 lb)	
Interface	1 HDMI,1 VGA	STORAGE		
Resolution	HDMI: 8CH: 1920×1080, 1280×1024, 1280×720	Internal HDD	1 SATA Port, up to 10TB capacity	
	16CH: 3840×2160, 2560×1440, 1920×1080, 1280×1024, 1280×720 VGA: 1920×1080, 1280×1024, 1280×720	AUXILIARY INTERF	AUXILIARY INTERFACE	
		USB	8CH:2 USB 2.0 16CH:1 USB 2.0 , 1 USB 3.0	
Multi-screen Display	When IP extension mode not enabled: 8CH: 1/4/8/9 16CH: 1/4/8/9/16 When IP extension mode enabled: 8CH: 1/4/8/9/16 16CH: 1/4/8/9/16/25	RS485	1 Port, for PTZ Control	
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording			

5MP AHD HA-DVR-5104-L


ENVIRONMENTAL			
Operating Conditions	-10°C ~ +55°C (+14°F ~ +131°F), 10~ 90% RH RH		
Storage Conditions	-20°C ~+70°C (-4°F ~+158°F), 0~90% RH		
CERTIFICATIONS			
Certifications	BIS certified, CE, FCC		


Ordering Information

ТҮРЕ	PART NUMBER	DESCRIPTION
DVR	HA-DVR-5108-L	8ch, 5MP DVR, 1 SATA, H.265+
DVR	HA-DVR-5116-L	16ch, 5MP DVR, 1 SATA, H.265+

Dimensions (mm)


HA-DVR-5108-L






5MP AHD HA-DVR-5104-L

HA-DVR-5116-L





For more information,

https://www.security.honeywell.com https://honeywellbuildings.in Tel:+91 124 4975000 Email: HBT-Indiabuildings@honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43, Block C, Sushant Lok Phase - I, Gurugram -122 002 Haryana India 5MP AHD HA-DVR-5108/16-L

