

# H2W2PC1M

## Network WDR 2MP People Counting Camera

### Performance Series 2 & 4 MP

Take Advantage of Honeywell's Performance Series of High Resolution IP Cameras

Honeywell is taking quality and reliability to the next level with the launch of the new Performance Series line of 2 and 4 MP cameras in addition to already existing 3MP and 4K cameras. The Honeywell cameras, including rugged dome, eyeball and bullet cameras offer incomparable picture clarity, hassle-free flexible system integration, and secure data transmission—and they install easily too!

### Superior HD Image Quality

- High picture quality with new 2 and 4 MP cameras for applications that require high details
- True WDR (120 dB) in 4 MP cameras ensures glare-free images
- True Day/Night provides vivid color images by day and clear black-and-white images at night using a removable IR cut filter
- Excellent low-light performance with 3D noise reduction, saving storage and bandwidth together with H.265 Profile codec

### Flexible Surveillance Solution

- A wide range of lenses and zoom options for all types of installations
- IR LEDs provide illumination in dimly lit or nighttime scenes
- Smart IR technology provides even distribution of IR (depending on camera models)
- Waterproof (IP66) and IK10 impact-resistant camera housing (rugged outdoor housings, depending on model)
- ONVIF Profile S and G compliant
- Cameras can use plug-and-play installation with Honeywell Performance Series NVRs

### Onboard Video Storage

- Supports microSDHC (Class 10) card for local video storage when network is interrupted (depending on model, card not included)



### Easy to Install and Use

- Built-in PoE or PoE+ (Power over Ethernet) eliminates separate power supply and associated wiring
- Remote configuration, motorized zoom adjustments and auto focus through web client or from the NVR
- Wide range of mounting options for the different camera housings include wall mounts, pendant mounts, pole and corner adapters and junction boxes support many types of security situations

### Market Opportunities

These fully featured attractive cameras are perfect for that requires high resolution True Day/Night cameras for any scenario. The Performance Series provides excellent picture clarity at minimal bandwidth while offering maximum protection against dust, dirt, and water. Boasting modern designs and offering up to 4MP high definition images, these cameras are suited for a wide range of security applications.

**Honeywell**

## H2W2PC1M

# Network WDR 2MP People Counting Camera

OPERATIONAL	
VIDEO STANDARD	NTSC/PAL
SCANNING SYSTEM	Progressive
IMAGE SENSOR	1/2.8" 2Megapixel progressive scan CMOS
NUMBER OF PIXELS (H × V)	1920(H) x 1080(V)
MINIMUM ILLUMINATION	0.08lux/F2.0( Color,30IRE) 0.04Lux/F2.0( B/W,30IRE)
S/N RATIO	More than 45dB
ELECTRONIC SHUTTER SPEED	1/3~1/100000s
IR DISTANCE	N/A
DAY/NIGHT	Auto(ICR) / Color / B/W
BACKLIGHT COMPENSATION	BLC / HLC / WDR
WHITE BALANCE	Auto/Natural/Street Lamp/Outdoor/Manual/Customized Region
GAIN CONTROL	0~100
WIDE DYNAMIC RANGE	120dB
NOISE REDUCTION	3D DNR
PRIVACY MASKING	Off / On (4 Areas, Rectangle)
MOTION DETECTION	Off / On (4 Zones Rectangle)
REGION OF INTEREST	Off / On (4 Zones)
FACE DETECTION	Supported
AUDIO DETECTION	Supported
PEOPLE COUNTING	Supported
LENS	2.1mm, F2.0 Fixed, Board-in
ANGLE OF VIEW	H: 128°, V: 70°
VIDEO	
VIDEO COMPRESSION	H.265/H.264H/Smart Codec/MJPEG (Sub Stream)
RESOLUTION	1080P(1920x1080)/1.3M(1280x960)/720P(1280x720)/D1(704x480/576)/CIF(352x240/288)
FRAME RATE	Main Stream: 1080P (1~50/60fps) Sub Stream: D1(1~50/60fps) Third Stream: 1080P(1~25/30fps)
BIT RATE CONTROL	CBR/VBR
BIT RATE	H.264: 24~9472Kbps H.265: 14~5632Kbps

NETWORK	
ETHERNET	RJ-45 (10-100Base-T)
SUPPORTED WEB BROWSERS	Internet Explorer (11.0+)
SUPPORTED OS	Windows® 7 32-bit/64-bit; Windows® 10 32-bit/64-bit
PROTOCOLS*	HTTP; HTTPS; TCP; ARP; RTSP; RTP; RTCP; UDP; SMTP; DHCP; DNS; PPPoE; IPv4/v6; QoS; UPnP; NTP; Bonjour; IEEE 802.1x; Multicast; ICMP; IGMP; TLS
INTEROPERABILITY	ONVIF Profile S/G/Q
MAXIMUM USERS ACCESS	20 Users
SECURITY	User account and password protection HTTPS, IP Filter, 128/256, SSH/Telnet closed, sFTP by default, PCIDSS compliance
EVENT	No SD card, SD card error, Capacity warning, Network disconnection, IP conflict, Illegal access
MICRO SD	Up to 128 GB microSDHC card, Class 10 (not included)
AUDIO	
COMPRESSION	G.711a /G.711Mu /AAC /G.726
INTERFACE	Built-in Mic
ELECTRICAL	
POWER SUPPLY	DC12V, PoE (802.3af)(Class 0)
POWER CONSUMPTION	<4.5W
MECHANICAL	
DIMENSIONS	Ø106mm×50.3mm (4.17"×1.98")
PRODUCT WEIGHT	0.32kg (0.71lb)
PACKAGE WEIGHT	0.46kg (1.01lb)
CONSTRUCTION	Die-cast aluminum housing with powder coat
CONSTRUCTION COLOR	RAL 9003 (White)
ENVIRONMENTAL	
OPERATING TEMPERATURE	-30°C ~ +60°C (-22°F ~ +140°F)
RELATIVE HUMIDITY	Less than 95%, non-condensing
INGRESS PROTECTION	IP66
IMPACT RESISTANCE	IK10

# H2W2PC1M

## Network WDR 2MP People Counting Camera


D79G>3FADK	
7? ;EE:A@E	855 BSf# " 4! 7@ ' " %\$
;? ? G@FK	7@' " #%" -&
E387FK	G> ( " 950-1, EN-62368-1
DA: E	7@' " ' *#

\* Some development may be required in specific user cases to support some of these protocols in the field as they mature over time.

### ORDERING

H2W2PC1M	Network WDR 2MP People Counting Camera, 1/2.8" CMOS, 2.1mm Fixed, PoE, IP66, H.265/H.264/Smart Codec, support mobile
----------	--

### DIMENSIONS



For more information,  
<https://honeywellbuildings.in>  
 Call : +91 124 4975000  
 Email: HBT-Indiabuildings@honeywell.com

**Honeywell HBT India Buildings**  
 Unitech Trade Center, 5th Floor, Sector-43,  
 Block C, Sushant Lok Phase - I,  
 Gurugram - 122 002  
 Haryana India

[www.honeywell.com](http://www.honeywell.com)

© 2020 Honeywell International Inc.

**H2W2PC1M**  
**3NETWORK WDR 2MP**  
**PEOPLE COUNTING CAMERA**  
**Honeywell**