

# HBW2GR3V/HBW2GR1V/ HBL2GR1V/ HBW4GR1V

Network TDN Low-Light WDR 2MP/4MP  
IR Rugged Bullet



HD Onvif\* | S G Q

OPERATIONAL	
VIDEO STANDARD	NTSC/PAL
SCANNING SYSTEM	Progressive scan
IMAGE SENSOR	<b>HBW2GR3V, HBW2GR1V, HBL2GR1V:</b> 1/2.8" 2Megapixel progressive scan CMOS <b>HBW4GR1V:</b> 1/3" 4 Megapixel progressive scan CMOS
NUMBER OF PIXELS (H×V)	<b>HBW2GR3V, HBW2GR1V, HBL2GR1V:</b> 2MP - 1920x1080 <b>HBW4GR1V:</b> 4MP - 2560x1440/2688x1520
MINIMUM ILLUMINATION	<b>HBW2GR3V, HBW2GR1V, HBL2GR1V:</b> Colour: 0.001Lux @f/1.6, B/W: 0Lux @f/1.6(IR on) <b>HBW4GR1V:</b> Colour: 0.01Lux @f/1.6, B/W: 0Lux @f/1.6(IR on)
S/N RATIO	50db minimum
ELECTRONIC SHUTTER SPEED	Auto/Manual, 1/3(4) ~1/100000s
IR DISTANCE	60m
DAY/NIGHT	Mechanical ICR (ON / OFF / AUTO selectable)
BACKLIGHT COMPENSATION	BLC / HLC / WDR / SAC (Scene Adaptive Control)
WIDE DYNAMIC RANGE (WDR)	<b>HBL2GR1V:</b> 140dB (50/60fps off) <b>HBW2GR1V, HBW2GR3V, HBW4GR1V:</b> 120dB (50/60fps off)
WHITE BALANCE	Auto/Natural/Street Lamp/Outdoor/Manual/ Customize Region
GAIN CONTROL	Auto/Manual
NOISE REDUCTION	3DNR
PRIVACY MASKING	4 configurable windows
ELECTRONIC IMAGE STABILIZATION	<b>HBW2GR3V, HBW2GR1V, HBW4GR1V:</b> Not supported <b>HBL2GR1V:</b> OFF/ON
DEFOG	Auto/Manual/Off
LENS	<b>HBW2GR3V:</b> 5-60mm MFZ, HALL IRIS(Extended Focal Depth), optical zoom 12x lens F1.6
	<b>HBW2GR1V, HBW4GR1V:</b> 2.7-13.5 mm MFZ, DC IRIS, optical zoom 5x lens F1.6
	<b>HBL2GR1V:</b> 2.7-12 mm MFZ, HALL IRIS(Extended Focal Depth), optical zoom 4x lens F1.6
ANGLE OF VIEW	<b>HBW2GR3V:</b> H: 62° - 6°, V: 34° - 4° <b>HBW2GR1V:</b> H: 110° - 32°, V: 59° - 19° <b>HBL2GR1V:</b> H: 102° - 35°, V: 54° - 21° <b>HBW4GR1V:</b> H: 110° - 30°, V: 53° - 18°
AUDIO/TWO-WAY	Line In/Out
ALARM INPUT/OUTPUT	2 In / 1 Out
ANALOG OUTPUT SUPPORT	Twin outputs (for adjustment only)
ETHERNET	<b>HBW2GR3V, HBW2GR1V, HBW4GR1V:</b> RJ-45 (10/100Base-T) <b>HBL2GR1V:</b> RJ-45 (100/1000Base-T)
IP SPECIFICATIONS	
VIDEO COMPRESSION	H.265+, H.265, H.264 and MJPEG bit rate control (CBR and VBR)
RESOLUTION	<b>16:9</b> <b>HBW2GR3V, HBW2GR1V, HBL2GR1V:</b> 1080p (1920×1080)/ 720p (1280×720) <b>HBW4GR1V:</b> 3M (2304×1296)/1080p (1920×1080)/ 720p (1280×720)
	<b>4:3</b> 1.3M (1280×960)/VGA (640×480)
	<b>OTHER</b> <b>HBW2GR3V, HBW2GR1V, HBL2GR1V:</b> D1 (704×576/704×480)/ CIF (352×288/352×240) <b>HBW4GR1V:</b> 4M (2688x1520)/(2560x1440)/D1 (704×576/704×480)/ CIF (352×288/352×240)

IP SPECIFICATIONS (CONT'D)		
FRAME RATE	MAIN STREAM	<b>HBW2GR3V, HBW2GR1V, HBL2GR1V:</b> 1080P (1~50/60fps WDR off) <b>HBW4GR1V:</b> 4M (1~25/30fps)
	SUB STREAM	<b>HBW2GR3V, HBW2GR1V, HBL2GR1V:</b> D1 (1~50/60fps WDR off) <b>HBW4GR1V:</b> D1 (1~25/30fps)
	THIRD STREAM	<b>HBW2GR3V, HBW2GR1V:</b> 1080P (1-25/30fps) <b>HBL2GR1V:</b> 1080P (1~50/60fps WDR off) <b>HBW4GR1V:</b> 4M(1~25/30fps)
		<b>HBW2GR3V, HBW2GR1V:</b> Simultaneous Main stream and Third stream at 1080P (Main stream +Third stream <=68fps, WDR off, 2nd stream off)
		<b>HBL2GR1V:</b> Simultaneous Main stream and Third stream at 1080P (Main stream at 50/60fps WDR off, Third stream at 50/60fps WDR off)
		<b>HBW4GR1V:</b> Simultaneous Main stream and Third stream at 4MP (Main stream +Third stream <=34fps, 2nd stream off)
AUDIO COMPRESSION		G.711a/ G.711Mu/ AAC/G.726
AUDIO STREAM		Full duplex, simplex
SUPPORTED WEB BROWSERS		IE11/Chrome(with application)/Firefox(earlier than 52.0 version)
SUPPORTED OS		Windows® 7 32-bit/64-bit; Windows® 10 32-bit/64-bit
SUPPORTED PROTOCOLS*		HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP; NTP; Bonjour; 802.1x; Multicast; ICMP; SNMP; SFTP
COMPATIBILITY		ONVIF Profile S, G and Q
MAXIMUM USERS ACCESS		20 users
SECURITY		User account and password protection HTTPS, IP Filter, IEEE 802.1x, Digest authentication, User access log, TLS1.2, AES-256, SSH/Telnet closed, FTP disabled, PCI-DSS compliance, Hardware chipset for private key
HEAT MAP		<b>HBL2GR1V:</b> Support
BUILT-IN ALARM & EVENT	EVENT TYPE	<b>HBW2GR1V, HBW2GR3V, HBW4GR1V:</b> Motion Detection/ Video Tampering/Face Detection/SD Card Error/SD Card Capacity Warning/Audio Detection/ Object Abandoned/Object Missing/ Tripwire/Intrusion
		<b>HBL2GR1V:</b> Motion Detection/Video Tampering/Face Detection/ SD Card Error/SD Card Capacity Warning/Audio Detection/Object Abandoned/Object Missing/People counting
	EVENT LINKAGE	Recording on SD card, Relay output, Email, Snapshot
	EVENT OUTPUT	ONVIF, ISOM
UPLOADABLE VIDEO ANALYTICS (HBL2GR1V ONLY)	BASIC	Trigger line/Intrusion/Loitering available now (Please download from www.honeywellvideo.com. Free of Charge, but please email to VALicensing@Honeywell.com to get license.)
	ADVANCED LICENSED ANALYTICS	IntrusionTrace/LoiterTrace for advanced applications coming soon. (Need to purchase separately)
	ANALYTICS OUTPUT	ISOM event output, Metadata
MICRO SD		Micro SDHC Capacity Max 32GB Micro SDXC Capacity Max 128GB
MICRO SD FUNCTION		Event trigger recording; Continuous and scheduled recording; Automatic recording when network fails
LANGUAGES SUPPORTED		English, Arabic, Czech, Dutch, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Simplified Chinese, Spanish, Turkish

# HBW2GR3V/HBW2GR1V/HBL2GR1V/HBW4GR1V


## NETWORK TDN LOW-LIGHT WDR 2MP/4MP IR RUGGED BULLET







ELECTRICAL	
POWER SUPPLY	PoE+(802.3at) Class 4/12VDC/AC24V
LONG DISTANCE POE SUPPORT	3X POE (300m @100Mbps)
AC FREQUENCY	50/60 Hz
POWER CONSUMPTION	HBW2GR3V: Max 17.3W; HBW2GR1V: Max 20.5W HBL2GR1V: Max 17W HBW4GR1V: Max 17.6W
AUXILIARY POWER SUPPLY	2.0W, DC12V (+/-5%)
MECHANICAL	
DIMENSIONS	11.1 x 4.3 in. (281.0 x 110.0 mm)
WEIGHT	Product weight: 4.70lb (2130g) Package Weight: 6.28lb (2847g)
CONSTRUCTION	Die-cast aluminum housing with powder coat
CONSTRUCTION COLOUR	RAL 9003 (White) and RAL 7022 (Grey)

ENVIRONMENTAL	
OPERATING TEMPERATURE	-40°F to 140°F (-40°C to 60°C)
RELATIVE HUMIDITY	0% to 95%, non-condensing Yes
GORE VENTS	IP 67
INGRESS PROTECTION	IK10
IMPACT RESISTANCE	Heater
HEATER, FAN OPTION	
REGULATORY	
EMISSIONS	FCC Part 15, CE (EN 55032); Complies with RCM (AS/NZS)
IMMUNITY	CE (EN 50130-4)
SAFETY	North America UL Listed to UL/CSA 60950-1, CE (EN 60950-1); North America UL Listed to UL/CSA 60950-22, CE (EN 60950-22)
ROHS	EN 50581

\* Some development may be required in specific user cases to support some of these protocols in the field as they mature over time.

## RECOMMENDED ACCESSORIES

SYSTEM INTEGRATION	
ONVIF support and open API software integration. Refer to <a href="http://www.onvif.org">www.onvif.org</a> for the ONVIF specification and the Honeywell Open Technology Alliance website ( <a href="http://www.security.honeywell.com/hota/">http://www.security.honeywell.com/hota/</a> ) to learn more about our open and integrated solutions.	

HOUSING AND MOUNTS		
HB4G-PM		Pole Mount Adapter
HB34G-CM		Corner Mount Adapter
HBG-BB		IP66 Back Box with Gasket (for Cable Termination)
HBG-FP		Front Lens Plate Replacement (if Vandalized)
HLR1001		IP over Coax Converter
HPOE3X		3X Long Distance POE Switch

## ORDERING

HBW2GR3V	Network TDN Low Light WDR IR Bullet Camera, 1/2.8" 2 Megapixel progressive scan CMOS, 5-60 mm MFZ, 4 IR LEDs, PoE+, H.265.
HBW2GR1V	Network TDN Low Light WDR IR Bullet Camera, 1/2.8" 2 Megapixel progressive scan CMOS, 2.7-13.5 mm MFZ, 4 IR LEDs, PoE+, H.265.
HBL2GR1V	Network TDN Intelligent Ultra WDR IR Bullet Camera, 1/2.8" 2 Megapixel progressive scan CMOS, 2.7-12 mm MFZ, 4 IR LEDs, PoE+, H.265
HBW4GR1V	Network TDN WDR IR Bullet Camera, 1/3" 4 Megapixel progressive scan CMOS, 2.7-13.5 mm MFZ, 4 IR LEDs, PoE+, H.265

# **HBW2GR3V/HBW2GR1V/HBL2GR1V/HBW4GR1V NETWORK TDN LOW-LIGHT WDR 2MP/4MP IR RUGGED BULLET**

## **DIMENSIONS**

For more information,  
<https://honeywellbuildings.in>  
Call: 1-800-103-0339  
Email: HBT-Indiabuildings@honeywell.com

**Honeywell HBT India Buildings**  
Unitech Trade Center, 5th Floor, Sector-43,  
Block C, Sushant Lok Phase - I,  
Gurgaon - 122 002

[www.honeywell.com](http://www.honeywell.com)

© 2020 Honeywell International Inc.

**HBW2GR3V/HBW2GR1V/  
HBL2GR1V/HBW4GR1V  
NETWORK TDN LOW-LIGHT  
WDR 2MP/4MP IR RUGGED  
BULLET**

**Honeywell**