HBW4PER2

WDR 4 MP IR Bullet Camera

Performance Series 2 & 4 MP

Take Advantage of Honeywell's Performance Series of High Resolution IP Cameras

Honeywell is taking quality and reliability to the next level with the launch of the new Performance Series line of 2 and 4 MP cameras in addition to already existing 3MP and 4K cameras. The Honeywell cameras, including rugged dome, eyeball and bullet cameras offer incomparable picture clarity, hassle-free flexible system integration, and secure data transmission—and they install easily too!



Superior HD Image Quality

- High picture quality with new 2 and 4 MP cameras for applications that require high details
- True WDR (120 dB) in 4 MP cameras ensures glare-free images
- True Day/Night provides vivid color images by day and clear blackand-white images at night using a removable IR cut filter
- Excellent low-light performance with 3D noise reduction, saving storage and bandwidth together with H.265 Profile codec

Flexible Surveillance Solution

- A wide range of lenses and zoom options for all types of installations
- IR LEDs provide illumination in dimly lit or nighttime scenes
- Smart IR technology provides even distribution of IR (depending on camera models)
- Waterproof (IP66) and IK10 impact-resistant camera housing (rugged outdoor housings, depending on model)
- ONVIF Profile S and G compliant
- Cameras can use plug-and-play installation with Honeywell Performance Series NVRs

Onboard Video Storage

• Supports microSDHC (Class 10) card for local video storage when network is interrupted (depending on model, card not included)

Easy to Install and Use

- Built-in PoE or PoE+ (Power over Ethernet) eliminates separate power supply and associated wiring
- Remote configuration, motorized zoom adjustments and auto focus through web client or from the NVR
- Wide range of mounting options for the different camera housings include wall mounts, pendant mounts, pole and corner adapters and junction boxes support many types of security situations

Market Opportunities

These fully featured attractive cameras are perfect for that requires high resolution True Day/Night cameras for any scenario. The Performance Series provides excellent picture clarity at minimal bandwidth while offering maximum protection against dust, dirt, and water. Boasting modern designs and offering up to 4MP high definition images, these cameras are suited for a wide range of security applications.



HBW4PER2 WDR 4 MP IR Bullet Camera

I

OPERATIONAL			
VIDEO STANDARD	NTSC/PAL		
SCANNING SYSTEM	Progressive scan		
IMAGE SENSOR	1/3" 4 MP CMOS		
NUMBER OF PIXELS (H × V)	2688×1520		
MINIMUM ILLUMINATION	0.03 lux color @ F1.4(Color, 1/3s, 30 IRE) 0 lux B/W with IR LEDs on @ F1.4		
S/N RATIO	> 45 dB		
ELECTRONIC SHUTTER SPEED	1/3(4) - 1/100,000 s		
IR DISTANCE	1/3(4) - 1/100,000 s		
DAY/NIGHT	Auto (ICR)/Color/BW		
BACKLIGHT COMPENSATION	BLC/HLC/WDR (120 dB)		
WHITE BALANCE	Auto/Natural/Street Lamp/Outdoor/Manual		
GAIN CONTROL	Auto/Manual		
WIDE DYNAMIC RANGE	True WDR (120 dB)		
NOISE REDUCTION	3D DNR		
PRIVACY MASKING	Up to 4 configurable zones		
MOTION DETECTION	Up to 4 configurable zones		
REGION OF INTEREST	Up to 4 configurable zones		
DIGITAL ZOOM	16x		
SMART IR	Auto/Manual		
LENS	2.7 – 13.5 mm, MFZ, F1.4		
ANGLE OF VIEW	104°-28° (H), 55°-16° (V)		
VIDEO			
VIDEO COMPRESSION	H.265+/H.265/H.264+/H.264		
RESOLUTION	4 MP (2688×1520), QHD (2560×1440), 3 MP (2304×1296), 1080p (1920×1080), SXGA (1280×1024), 1.3 MP (1280×960), 720p (1280×720), D1 (704×576/704×480), VGA (640×480), CIF (352×288/352×240		
FRAME RATE	4 MP at 1 – 20fps, 3 MP at 1 – 25/30fps D1/CIF at 1 – 25/30fps		
BIT RATE CONTROL	CBR/VBR		
BIT RATE	H.265: 12K – 8448 Kbps H.264: 32K – 10240 Kbps		

NETWORK				
ETHERNET	RJ-45 (10/100BASE-T)			
SUPPORTED WEB BROWSERS	Internet Explorer (11.0+)			
SUPPORTED OS	Windows 7 32-bit			
PROTOCOLS*	IPv4/v6, TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, SSL, FTP, SMTP, DHCP, PPPoE, UPnP, SNMP v2/v3, Bonjour, DNS, DDNS, IEEE 802.1X, QoS, NTP			
INTEROPERABILITY	ONVIF Profile S, Profile G			
MAXIMUM USERS ACCESS	20 Users			
SECURITY	User account and password protection, HTTPS, IP filter, IEEE 802.1X, digest authentication, user access log, TLS1.2, AES-256, SSH/Telnet closed, FTP disabled			
EVENT	Network disconnection, IP address conflict, illegal access, video tampering, motion detection			
EVENT NOTIFICATION	Record (SD card, NAS, and FTP), relay output, email, snapshot			
MICRO SD	Up to 128 GB microSDHC card, Class 10 (not included)			
ELECTRICAL				
POWER SUPPLY	PoE (802.3af) Class 0, 12 VDC			
POWER CONSUMPTION	5.7 W max. (IR LEDs on)			
MECHANICAL				
DIMENSIONS	8.46" × 3.56" (214.8 mm × 90.4 mm)			
PRODUCT WEIGHT	1.51 lb (0.685 kg)			
PACKAGE WEIGHT	1.90 lb (0.86 kg)			
CONSTRUCTION	Die-cast aluminum housing with powder coat			
CONSTRUCTION COLOR	RAL 9003 (White)			
ENVIRONMENTAL				
ENVIRONMENTAL OPERATING TEMPERATURE	-22°F to 140°F (-30°C to 60°C)			
OPERATING	-22°F to 140°F (-30°C to 60°C) Less than 95%, non-condensing			
OPERATING TEMPERATURE	Less than 95%, non-condensing			

HBW4PER2 WDR 4 MP IR Bullet Camera

D79G>3FADK	
EMISSIONS	FCC Part15B, EN 55032
IMMUNITY	EN 50130-4
SAFETY	EU: EN 60950-1 North America UL listed to UL/CSA 60950-1
ROHS	EN 50581

RECOMMENDED ACCESSORIES


SYSTEM COMPATIBILITY		MOUNTS AND ACCESSORIES		
HEN*4	8/16/32/64-channel Focus 4K NVRs (H.264/ H.265)	HQA-PM2**		Pole Mount Bracket
HEN*2	4/8/16-channel Performance Series NVRs (H.264)	HB34S2-CM**		Corner Mount Bracket
 * Pre-installed storage (TB). ** The HBS2-BB junction box must be used when installing the camera to HQA-PM2 or HB34S2-CM. 		HBS2-BB		Junction Box

ORDERING

HBW4PER2

Network WDR 4 MP IR Bullet Camera, 1/3" CMOS, 2.7–13.5 mm MFZ, 4 IR LEDs, PoE, H.265+

DIMENSIONS



For more information,

https://honeywellbuildings.in Call : +91 124 4975000 Email: HBT-Indiabuildings@honeywell.com

Honeywell HBT India Buildings

Unitech Trade Center, 5th Floor, Sector-43, Block C, Sushant Lok Phase - I, Gurugram - 122 002 Haryana India

www.honeywell.com



HBW4PER2

WDR4MPIR

BULLET CAMERA