

HIE2PI-S


PERFORMANCE LITE IP SD CAMERAS 2MP IP IR EYEBALL CAMERA

Honeywell's new Performance Lite IP camera series is aimed to provide high quality surveillance as an affordable offering for the small and medium businesses including small retail shops, gyms, schools, residential homes, etc.

The new series includes 2MP IR cameras, with SD card slot, in both eyeball and bullet configurations with fixed and variable lens options to cater to all kinds of customer applications. The cameras come with IR LEDs so as to provide effective and efficient surveillance even during the night time. The cameras are IP67 rated that makes them resilient for outdoor applications as well.



HIE2PI-S



Sensor



Min.
Illumination




DWDR




Motion
Detection



Day & Night



AWB



POE



Water-proof

KEY FEATURES

- 2MP full real time recording
- H.265 Codec Compression
- Built-in microSD card slot (upto 128GB)
- Upto 50m IR distance
- 3D DNR, DWDR
- IP 67 certified
- Support dual streams
- Onvif Profile S/G compliant

HIE2PI-S

PERFORMANCE LITE IP CAMERAS

SPECIFICATIONS

CAMERA	
Image Sensor	1/2.9 CMOS
Number of Pixels (H x V)	1920 x 1080
Electronic Shutter	1/25s ~ 1/ 100000s
Iris	Fixed Iris
Min Illumination	0.007 lux @F1.2, AGC ON; 0 lux with IR
Lens	3.6 mm @F1.6, Angle of View: 92 deg
Day & Night	TDN
Wide Dynamic Range	Digital WDR
IMAGE	
Video Compression	H.265 / H.264 / MJPEG
Compression Standard	Baseline / Main / High Profile
Resolution	1080p, 720p, D1, CIF
Number of Streams	2 (main stream ,sub stream)
Resolution	Main stream: 50Hz: 1080p / 720p @(1-25fps) Sub stream: 50 Hz: D1/CIF/480 x 240 @(1-25fps)
Bit Rate	256 Kbps ~ 4 Mbps
Encode Mode	CBR / VBR (Freely adjustable in CBR, 5 levels in VBR)
Image Settings	ROI, Saturation, Brightness, Contrast, Wide Dynamic, Sharpen, Noise reduction, De-fog, Watermark, Heartbeat
ROI	3 ROI
INTERFACES	
Network	RJ45
FUNCTIONS	
Remote Monitoring	IE / Firefox Browsing, CMS control
Online Connection	Simultaneous monitoring for upto 4 users; support multi-stream real time transmission
Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, DDNS, SMTP, FTP, HTTPS
Interface Protocol	ONVIF S, ONVIF G
Motion Alarm	Supported
IR Distance	20 - 30 m
IP Rating	IP67
OTHERS	
Power Supply	DC 12V / PoE
Power Consumption	< 5 W
IR Consumption ON	< 10 W

HIE2PI-S

PERFORMANCE LITE IP CAMERAS


Operating Temperature -30 deg C to 60 deg C, 90% humidity

Dimensions (mm) 82.8 x 94.6

Weight 450g

DIMENSIONS

HIE2PI-S



ORDERING

HIE2PI	1/2.7" CMOS Sensor, 2 MP Fixed lens, SD Slot, TDN, DWDR, 3.6 mm, 12 VDC / PoE
--------	---

For more information,
<https://honeywellbuildings.in>
Call : +91 124 4975000
Email: HBT-Indiabuildings@honeywell.com

Honeywell HBT India Buildings
Unitech Trade Center, 5th Floor, Sector-43,
Block C, Sushant Lok Phase - I,
Gurugram - 122 002
Haryana India

www.honeywell.com

© 2020 Honeywell International Inc.

HIE2PI-S
PERFORMANCE LITE IP
CAMERAS

Honeywell