HON-BIOEM-5000TA/ HON-BIOMI-5000TA

- POE Supported*
- Sleek Design
- Built-in audible buzzer
- Host LED control
- Hidden mounting screws deter vandalism
- Wiegand Output Interface
- Extended battery*
- Wiegand IN & OUT
- CE,FCC & BIS CERTIFIED



SYSTEM OVERVIEW

HON-BIOEM-500TA is a fingerprint time & attendance terminal With SSR report(self-service Report) stored in the time clock. The 2.8inch TFT screen can display more information vividly, including fingerprint image and verification result .

TCP/IP communication is a standard function which makessure the data transmission between terminal and PC can be easily done within few seconds. Internal backup battery insures the device work normally when the power cuts off suddenly.

SPECIFICATIONS

Part code	Description
HON- BIOEM- 5000TA	Honeywell Bio Terminal with EM CARD
HON– BIOMI - 5000TA	Honeywell Bio Terminal with MIFARE CARD
5000 – POE	POE module for 5000TA
5000 - BAT	Extended battery supported for 5000TA




Product	Mode No	HON-BIOEM-5000TA/ (EM card) HON-BIOMI-5000TA (Mifare Reader)
Main	Biometric RFID	Fingerprint 125kHz EM
Capacity	Max User(1:N) Max Fingerprint (1:N) Max Record	1,0000 1,0000 (1 Fingerprint Per user) 100,000
Interface	TCP/IP USB RS232 Relay Wiegand POE (Optional) Wi-Fi (Optional	10/100 M USB 2.0 (Host) 1 port for external printer 2 relays 1ch In & Out 802.3 at 28W 802.11 B/G/N
Hardware	LCD Sound Operating Temp. Operating Humidity Power Certificates	2.8" TFT Display 24-bit 0 °C- 45 °C 20% ~ 80% DC 12V 3A CE, FCC, BIS
Function	Standard	Automatic Status Switch, Sel-fService Query, T9 Input, 9 Digit User ID ,Lock sensor Exit button, Alarm, duress FP, Mult-verification
	Optional	Removable backup battery
Compatibility		Easy Web 2.0 EasyTime 3.0

For more information,

https://honeywellbuildings.in Call: 1-800-103-0339 Email: HBT-Indiabuildings@honeywell.com

Honeywell HBT India Buildings Unitech Trade Center, 5th Floor, Sector-43, Block C, Sushant Lok Phase - I, Gurgaon - 122 002

www.honeywell.com



HON-BIO-EM-5000TA/ HON-BIOMI-5000TA

